

# [EN] Migrating the dLibra Server System between Machines

Below we describe the actions to be taken in order to transfer the dLibra system server from one (computer) server to another. The servers can operate under the control of any operating systems. Also, it does not matter whether they are virtual servers or physical machines.

It is assumed that all services of the dLibra system server are installed on the server. You will find more information about the services of the dLibra system server in chapter [13. Scaling the dLibra System](#).

## Transferring the dLibra Server Application and Data

Server configuration:

Parameter	Source server	Target server
The type of the operating system	Linux	Windows
The location of the dLibra server applications	<i>/dlibra/dlibra-server</i>	<i>c:\dlibra\dlibra-server</i>
The location of the directory with the content of digital objects	<i>/dlibra/content/files</i>	<i>c:\dlibra\content\files</i>
The location of the directory with search indexes	<i>/dlibra/content/index</i>	<i>c:\dlibra\content\index</i>
The location of the directory with a copy of search indexes	<i>/dlibra/content/index_backup</i>	<i>c:\dlibra\content\index_backup</i>
The location of the directory with the JPG cache	<i>/dlibra/content/jpg-cache</i>	<i>c:\dlibra\content\jpg-cache</i>
The location of the directory with the ZIP cache	<i>/dlibra/content/zip-cache</i>	<i>c:\dlibra\content\zip-cache</i>
The host IP address with the dLibra server	<i>150.254.100.1</i>	<i>150.254.100.2</i>

Before beginning the migration of the dLibra system, the target server should be configured in a similar way to the source server. First of all, Java Runtime Environment (JRE) 1.8 from the Oracle company (formerly Sun Microsystems) must be installed, and connections must be enabled on the ports required by the dLibra system server.

1. Turn off the dLibra system on the source server.
2. Copy the server application directory of the dLibra system server from the source server to the target server.
3. Copy the directories with: the content of digital objects, search indexes, and a copy of search indexes. The ZIP and JPG cache directories do not have to be copied.
4. Update the configuration files:

- *c:\dlibra\dlibra-server\conf\cs\service.properties:*

- `contentDirectory=c:\\dlibra\\content\\files`

- `zip.cachePath=c:\\dlibra\\content\\zip-cache`

- `jpg.cachePath=c:\\dlibra\\content\\jpg-cache`

- *c:\dlibra\dlibra-server\conf\lucene.properties:*

- `indexDirectory=c:\\dlibra\\content\\index`

- `indexBackupDirectory=c:\\dlibra\\content\\index_backup`

If the network address (IP or domain address) of the target server is changed, additional actions must be carried out. If the address is not changed or is not used in the configuration, those actions should be skipped.

1. In file *c:\dlibra\dlibra-server\conf\server.xml*, update the server address – attribute *serverHost* of the server element. In our case:

```
<dlibra serverHost="150.254.100.2" serverPort="10051">
```

2. In the database, in table SYS\_SERVICES, update the values in column SER\_HOST for the records of the moved services (all except for the ss service available on the 127.0.0.1 host and except for the ps service).
3. In the Reader Application, in file dlibra-webapp/WEB-INF/conf/services.properties, update the value of parameter ss.url, by changing it to //150.254.100.2:10051/ss

Having carried out those actions, we can start up the dLibra system server on the new server, in accordance with the description in chapter [01. Starting up the dLibra System Server](#).

## Moving the Database

If the database has also been moved, the connection parameters in file `c:\dlibra\dlibra-server\conf\database.properties` should be updated.